



CATV range equipment

Optical receivers

- electronic setting of all parameters
- AGC based on optical input level
- thermal compensation of RF output level drift
- digital indication of optical input level and other parameters
- die-cast housing
- connectors:
RF output and test - type F
optical - SC/APC

OD001A
output level 94 dB μ V

OD002
output level 106 dB μ V

OD100
output level 113 dB μ V



Technical specifications			
TYPE	OD001A	OD002	OD100
Ordering number	02823	02824	02825
Optical wave lenght		1100-1600 nm	
Optical input level (AGC range)		-7 ...2 dBm	
Optical return loss		> 40 dB	
Noise current density		$\leq 7.0 \text{ pA}/\sqrt{\text{Hz}}$	
Frequency range		47-862 MHz	
Impedance		75 Ω	
Return loss		$\geq 18 \text{ dB}$ at 40 MHz-1.5 dB/oct	
Frequency response		$\pm 0.75 \text{ dB}$	
Output level (AGC controlled, 4.9% OMI)	94 dB μ V	106 dB μ V	115 dB μ V
Output level (CTB, EN50083-3)*	99 dB μ V (42 ch.)	107 dB μ V (42 ch.)	113 dB μ V (42 ch.)
Output level (CSO , EN50083-3)*	101 dB μ V (42 ch.)	110 dB μ V (42 ch.)	113 dB μ V (42 ch.)
Interstage attenuator	pr.	0-10 dB by 0.5 dB step	0-15.5 dB by 0.5 dB step
Interstage equalizer	pr.	0/5/10 dB	0-15.5 dB by 0.5 dB step
Loss in test point		-20 dB $\pm 0.7 \text{ dB}$	
Power consumption	230V~50/60 Hz 5 W or DC 12-18 V 4 W	230V~ 50/60 Hz 6 W	230 V~ 50/60 Hz 12 W
Operating temperature range		-20° \div + 50° C	
Dimensions/Weight (packed)	185.5x95x47 mm/0.9 kg		213x138x76 mm (with fixing ears)/1.35 kg

* output level (CTB, CSO) is measured with 5 dB (6 dB - OD100) interstage equalizer

pr. software control

4.05

